Package: OmicsPrepR (via r-universe)

October 8, 2026

Title Unified Preprocessing Toolkit for Proteomics and Metabolomics

Version 0.1.0

Maintainer Isaac Osei <ikemillar65@gmail.com>

Description An integrated R package providing unified workflows for quality control, normalization, and visualization of proteomic and metabolomic data. The package simplifies preprocessing through automated imputation, scaling, and PCA-based exploratory analysis, enabling researchers to prepare omics datasets efficiently for downstream statistical and machine learning analyses.

License GPL-3

Encoding UTF-8

Imports ggplot2, stats, utils

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

URL https://github.com/ikemillar/OmicsPrepR

BugReports https://github.com/ikemillar/OmicsPrepR/issues

Repository https://ikemillar.r-universe.dev

Date/Publication 2025-11-01 17:35:27 UTC

RemoteUrl https://github.com/ikemillar/omicsprepr

RemoteRef HEAD

RemoteSha 0a004715a60718d53565ef7469437edbb750ceb2

Contents

export_clean 2
impute_missing 3
integrate_omics 3
load_omics 4
normalize_omics 4

Index **5**

`export_clean` *Export Cleaned Omics Data*

Description

Exports processed omics data to a CSV file for downstream analysis.

Usage

```
export_clean(data, file_path)
```

Arguments

`data`	A data frame containing the cleaned omics data.
`file_path`	A character string specifying the output file path.

Value

A message confirming export success.

Examples

```
## Not run:
export_clean(my_cleaned_data, "output/cleaned_data.csv")

## End(Not run)
```

impute_missing *Impute Missing Values in Omics Data*

Description

Impute Missing Values in Omics Data

Usage

```
impute_missing(data, method = c("mean", "median"))
```

Arguments

data	Omics data frame with missing values.
method	Imputation method ("mean", "median").

Value

Data frame with imputed values.

integrate_omics *Integrate Proteomic and Metabolomic Data*

Description

Integrate Proteomic and Metabolomic Data

Usage

```
integrate_omics(prot, met)
```

Arguments

prot	Proteomics data frame.
met	Metabolomics data frame.

Value

A merged data frame with common samples.

load_omics *Load Proteomics or Metabolomics Data*

Description

Load Proteomics or Metabolomics Data

Usage

```
load_omics(file, type = c("proteomics", "metabolomics"))
```

Arguments

file	Path to data file (.csv or .tsv)
type	Type of omics data ("proteomics" or "metabolomics")

Value

A data frame containing the omics dataset

Examples

```
## Not run:
data <- load_omics("data.csv", type = "proteomics")

## End(Not run)
```

normalize_omics *Normalize Omics Data*

Description

Normalize Omics Data

Usage

```
normalize_omics(data, method = c("zscore", "log2"))
```

Arguments

data	A numeric data frame of omics values.
method	Normalization method ("zscore", "log2", "quantile").

Value

Normalized data frame.

Index

export_clean, 2

impute_missing, 3
integrate_omics, 3

load_omics, 4

normalize_omics, 4